

Semi-automated blood coagulation analyser CA-104

Simplifying
coagulation testing



Design and specifications may be subject to change due to further product development.

Registered under Act 737
Registration No:
NDA1335722-87555

Sysmex Asia Pacific Pte Ltd
Tel +65 6221-3629 Fax +65 6221-3687
www.sysmex-ap.com

Sysmex India Pvt. Ltd
Tel +91 (22) 6112-6666
www.sysmex.co.in

PT Sysmex Indonesia
Tel +62 (21) 3002-6688 Fax +62 (21) 3002-6699
www.sysmex.co.id

Sysmex (Malaysia) Sdn Bhd
Tel +60 (3) 5637-1788 Fax +60 (3) 5637-1688
www.sysmex.com.my

Sysmex New Zealand Ltd
Tel +64 (9) 630-3554
www.sysmex.co.nz

Sysmex (Thailand) Co., Ltd
Tel +66 (2) 032-2536 Fax +66 (2) 116-5396
www.sysmex.co.th

Sysmex Philippines Inc.
Tel +63 (2) 621-2460 Fax +63 (2) 621-2432
www.sysmex.com.ph

Sysmex Vietnam Co., Ltd
Tel +84 (8) 3997-9400 Fax +84 (8) 3997-9405
www.sysmex.com.vn

Sysmex Vietnam Co., Ltd (Hanoi Branch)
Tel +84 (4) 3776-7020 Fax +84 (4) 3776-7022
www.sysmex.com.vn

Sysmex Australia Pty Ltd
Tel +61 (2) 9016-3040
www.sysmex.com.au

CA-104 Your Straightforward, Compact Coagulation Analyser



Together with high quality reagents, it provides a reliable coagulation solution, not only for low volume testing, but also as a backup for fully automated system that requires a different optical method

Reagent system

- PT** • Thromborel S, Dade Innovin
APTT • Dade Actin, Dade Actin FS, Dade Actin FSL, Pathromtin SL
TT • Thromboclotin, Test Thrombin Reagent
Fbg • Multifibren U



Ideal for laboratories that require minimum manual intervention in performing routine coagulation assays. It is designed to simplify coagulation testing; making it more standardized and reproducible

- Coagulation testing is made easy with built-in timer, temperature control, and auto-start and timing of measuring process
- Easy to use with pre-programmed methods
- Objective detection of clot formation
- Automatic light intensity adjustment according to the turbidity of the plasma, making it possible to measure icteric or lipemic plasma reliably
- Sophisticated standard curve tool to maintain accuracy and precision
- Increase throughput with short incubation time
- A technology that requires only half the sample and reagent volume for testing as compared to manual method



Turbidensitometric Measuring Principle

A light beam passes through the cuvette containing the test plasma onto a photo detector. Any change in the intensity of the transmitted light, i.e., light increase or decrease, is converted into an electric signal

The stirrer mix the reagent and plasma in the cuvette. And at the same time creates a small whirl through the mixer movement to ensure even the smallest fibrin clot is formed in front of the photo detector

Once the start reagent is added, the lamp intensity automatically adjusts up or down according to the turbidity of the sample

This stirring action and optical measurement constitute the basic features of the turbidensitometric measuring principle

